

DS-2TP21B-6AVF/W

Body Temperature Measurement Camera



- 160 × 120 Resolution (Thermal), and 8 MP Resolution (Optical)
- 640 × 480 Resolution 3.5" LCD Touch Display
- Temperature Measurement Range: 86° to 113° F (30° to 45° C)
- Temperature Measurement Accuracy: ±0.9° F (±0.5° C) at 4.92 feet to 8.2 feet (1.5m to 2.5m)
- **Display Fusion of Thermal View and Optical View**
- **Supports Color Highlight Alarm and Audio Alarm**
- Working temperature: 59° to 95° F (15° to 35° C)

The Hikvision DS-2TP21B-6AVF/W handheld thermal camera is specially designed for body temperature measurement. It is equipped with a 160×120 resolution thermal detector. It is capable of discovering and tracking people with elevated body temperatures in crowded public areas and can be widely used in places such as customs, airport, schools, and hospitals for inspection and quarantine.

Available Models: DS-2TP21B-6AVF/W























Specifications

<u>opecinications</u>	
	DS-2TP21B-6AVF/W
Thermal Module	
	Uncooled focal plane arrays
	25 Hz: 160 × 120
Pixel Pitch	
Response Waveband	
	540 mk (@ 25° C. F#=1.0)
	5° × 18.7°
	6.2 mm (manual focus)
	5.2 iiii (iiiiiida 16003) 2.74 mrad
Aperture	
Optical Module	
	Configurable: 2 MP, 5 MP, 8 MP
Video Resolution	
	640 × 480 resolution 3.5" LCD touch display
	Black hot, white hot, red hot, rainbow, ironbow, fusion, rain
Image Display	Thermal: 1x, 2x, 4x
	Thermal/optical/fusion image/picture-in-picture
Distance in Distance	Supports thermal view in optical view
	Supports thermal view and optical view combined
	Supports on-board video recording
Thermography	
	Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography
	86° to 113° F (30° to 45° C)
	±0.9° F (±0.5° C)
Battery	
ваттегу туре	Dismountable and rechargeable li-ion battery
Battery Operating Time	5 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off
Chauser	4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Built-in memory module (16 GB)
	Thermal/optical/fusion image
	Thermal/optical/fusion image Thermal/optical/fusion image
	Supported
Text Comment	
Voice Comment	
Language	
General	5 VDC/2 A
Power Consumption	
Power Consumption Hardware Interface	
	59° to 95° F (15° to 35° C)
Working remperature Protection Level	סס נוסט ר(בס נוסס כן
Drop Test Height	6.56 π (2 m) 9.6" × 3.9" × 4.1" (244 mm × 100 mm × 104 mm)
imension	
Weight	With battery: 1.44 lb (653 g) Without battery: 1.13 lb (511 g)
	WILLIOUIL DALLETY. 1.13 ID (311 g)

Dimensions







